



GENUINE ORIGINAL GERMAN BEARINGS CO.,LTD



30,000 mm x 72,000 mm x 19,000 mm NTN
6306LLUNR deep groove ball bearings

Bearing No. 6306LLUNR

6306LLUNR Bearing 2D drawings and 3D CAD models

Size	30x72x19 mm
Bore Diameter	30,000 mm
Outer Diameter	72,000 mm
Width	19,000 mm
d	30,000 mm
D	72,000 mm
B	19,000 mm
C	19,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359575514
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric



GENUINE ORIGINAL GERMAN BEARINGS CO.,LTD

Long Description	30MM Bore; 72MM Outside Diameter; 19MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal With Snap Ring -20 To 120 Deg C Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.763
Outside Diameter	2.835 Inch 72 Millimeter
Outer Race Width	0.748 Inch 19 Millimeter
Bore	1.181 Inch 30 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	30 mm
precision rating:	ISO Class 0
outside diameter:	72 mm
finish/coating:	Uncoated
overall width:	19 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	19 mm



GENUINE ORIGINAL GERMAN BEARINGS CO.,LTD

row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	19 mm
snap ring included:	With Snap Ring
maximum rpm (grease):	6600 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	6600 RPM
dynamic load capacity:	26700 N
series:	63
static load capacity:	15000 N
manufacturer product page:	Click here